Amendments to the Claims:

This listing of claims will replace all prior versions of claims in the application.

LISTING OF CLAIMS:

1. (Previously Presented) A position sensor for sensing the position of a piston movable within a cylinder comprising:

a frame;

a spool rotatably mounted to the frame;

a cable windable about the spool and having a distal end adapted to be affixed to the piston, wherein the spool rotates as the cable winds and unwinds in relation to the movement of the piston, said spool operable to travel along a substantially linear path in response to the rotational movement of the spool;

and a sensing means adapted to sense the position of the spool along its substantially linear path.

- 2. (Original) The position sensor of claim 1 wherein the sensing means includes a Hall-effect transducer operably disposed to a target magnet movable in cooperation with the movement of the spool.
- 3. (Original) The position sensor of claim 2 wherein said Hall-effect transducer is mounted to the exterior of said frame.
- 4. (Original) The position sensor of claim 1 wherein the spool travels along a linear path that is parallel to the rotational axis of the spool.
- 5. (Original) The position sensor of claim 1 wherein the spool has a threaded engagement with the frame to cause the linear travel of the spool as the spool rotates.
- 6. (Original) The position sensor of claim 1 wherein the spool has a threaded extension that is threadedly engaged with a threaded opening in the frame.

- 7. (Original) The position sensor of claim 6 wherein the frame has a bushing having threads formed therein and the threaded extension has mating threads.
- 8. (Original) The position sensor of claim 1 wherein the pitch of the threaded engagement causes the spool to travel a distance along its linear path about the width of the cable for each 360 degrees of rotation of the spool.
- 9. (Original) The position sensor of claim 6 wherein said sensor includes a backlash mechanism to prevent backlash within the threaded engagement between the threaded extension and the frame.
- 10. (Original) The position sensor of claim 9 wherein the backlash mechanism comprises a spring adapted to create a constant bias on the threaded extension to force the threaded extension against the threaded opening in the frame to prevent backlash therebetween.

11. (Cancelled)

- 12. (Previously Presented) The position sensor of claim 10 wherein the backlash mechanism comprises an arm pivotally affixed to the frame, the arm adapted to engage the threaded extension to create a constant bias on the threaded extension to force the threaded extension against the threaded opening in the frame to prevent backlash therebetween and wherein the sensing means comprises a sensor affixed to the arm to sense the position of the spool.
- 13. (Original) The position sensor of claim 12 wherein there is a magnet affixed to the frame and the sensor comprises a Hall effect sensor that cooperates with the magnet to sense the position of the arm.
- 14. (Original) The position sensor of claim 1 wherein a recoil spring biases the rotational movement of the spool to cause the cable to wind up on the spool.
- 15. (Original) The position sensor of claim 14 wherein the recoil spring has one end affixed to the rotatable spool and another end is fixed with respect to the frame.

- 16. (Previously Presented) The position sensor of claim 15 wherein the recoil spring is a spiral spring having an outer end and an inner end and wherein the outer end is affixed to the rotatable spool and the inner end is fixed with respect to the frame.
- 17. (Previously Presented) The position sensor of claim 16 wherein the inner end of the spiral spring is affixed to a hub that is rotatably fixed with respect to the frame but is movable linearly along with the linear travel of the spool.
- 18. (Original) The position sensor of claim 17 wherein the spool has a hollowed out area and the spiral spring is located within the hollowed out area within the spool.
- 19. (Original) The position sensor of claim 18 wherein a cover plate covers the hollowed out area enclosing the spiral spring within the spool.
- 20. (Previously Presented) A position sensor for sensing the position of a piston movable within a cylinder, the sensor comprising a frame, a spool rotatably affixed within the frame about a central axis of rotation, a feed point opening in said frame located in close proximity to the spool, and a cable passing through the feed point opening having one adapted to be affixed to the piston and adapted to be wound around the spool to form a plurality of individual windings adjacent to but not overlapping each other, said spool adapted to move linearly along its axis of rotation as the cable is wound or unwound about the spool.
- 21. (Original) The position sensor of claim 20 wherein the spool is threadedly engaged to the frame.
- 22. (Original) The position sensor of claim 20 wherein the spool has a threaded extension extending therefrom and which is threadedly engaged through a threaded opening in the frame.

- 23. (Original) The position sensor of claim 22 wherein the linear movement of the spool through one full rotation is about one cable width.
- 24. (Original) The position sensor of claim 22 wherein the extension has male threads that interengage female threads formed in the frame.
- 25. (Previously Presented) The position sensor of claim 22 wherein a backlash mechanism creates a constant force against the threaded extension to prevent backlash in the threaded engagement between the threaded extension and the frame.
- 26. (Original) The position sensor of claim 23 wherein the recoil spring has an outer end affixed to the spool and an inner end that is prevented from rotating but can move linearly with respect to the frame.
- 27. (Original) The position sensor of claim 26 wherein inner end is affixed to a hub that is linearly movable but is prevented from rotational movement with respect to the frame.
- 28. (Original) The position sensor of claim 27 wherein the hub is affixed to the frame by means of at least one pin that extends between the hub and the frame and the at least one pin slidingly interfits in the hub to allow the hub to move linearly with respect to the frame.
- 29. (Previously Presented) A method of sensing the position of a piston moving within a cylinder by a sensor comprising a rotatable spool and a cable windable about the spool, the cable having a distal end adapted to be affixed to the piston, comprising the steps of:

linearly translating the spool in correlation to the rotational movement of the spool.

30. (Original) The method of claim 29 wherein the linear translation of the spool maintains cable windings in substantial alignment with the distal end.

- 31. (Original) The method of claim 29 further comprising the step of temperature compensating a signal provided by the sensor.
- 32. (Original) The method of claim 29 further comprising the step of offset adjusting the sensing means.
- 33. (Original) The sensor of claim 1 wherein the sensing means further includes a magnet in moveable cooperation with the rotating spool and adapted to translate linearly proximate the Hall effect sensor such that the Hall effect sensor provides a position related signal relative to a position of the magnet.
- 34. (Original) The sensor of claim 33 further comprising an adjustment mechanism to adjust an offset between the Hall effect sensor and the magnet.
- 35. (Original) The sensor of claim 1 wherein the sensing means includes temperature sensitive elements, the sensor further comprising a temperature compensation element.
- 36. (Original) The sensor of claim 35 wherein the temperature compensation element includes an electronic compensation circuit.
- 37. (Original) The sensor of claim 35 wherein the compensation element comprises a temperature sensitive metal.
- 38. (Previously Presented) The sensor of claim 33 further comprising a reference Hall-effect chip mounted in fixed relation to the magnet and a circuit operable to compensate for a difference in outputs for the Hall-effect sensor and the reference Hall-effect chip.

39. (Previously Presented) A position sensor comprising: a frame;

a spool rotatably mounted to the frame;

a cable windable about the spool and having a distal end adapted to be affixed to the object to be sensed, wherein the spool rotates as the cable winds and unwinds in relation to the movement of the object, said spool operable to travel along a substantially linear path in response to the rotational movement of the spool;

and a sensing means adapted to sense the position of the spool along its substantially linear path, wherein the sensing means includes a Hall-effect transducer mounted to the exterior of the frame and operably disposed to a target magnet movable in cooperation with the movement of the spool.

40. (Previously Presented) A position sensor comprising:
a frame having a bushing having threads formed therein;
a spool rotatably mounted to the frame, the spool having a threaded
extension having mating threads with the bushing and is threadedly engaged with the
threaded bushing;

a cable windable about the spool and having a distal end adapted to be affixed to the object to be sensed, wherein the spool rotates as the cable winds and unwinds in relation to the movement of the object, said spool operable to travel along a substantially linear path in response to the rotational movement of the spool;

and a sensing means adapted to sense the position of the spool along its substantially linear path.

41. (Previously Presented) A position sensor comprising: a frame;

a spool rotatably mounted to the frame, the spool having a threaded extension having mating threads with the bushing and is threadedly engaged with the threaded bushing;

a cable windable about the spool and having a distal end adapted to be affixed to the object to be sensed, wherein the spool rotates as the cable winds and

unwinds in relation to the movement of the object, said spool operable to travel along a substantially linear path in response to the rotational movement of the spool;

and a sensing means adapted to sense the position of the spool along its substantially linear path

the sensor further including a backlash mechanism to prevent backlash within the threaded engagement between the threaded extension and the frame, the backlash mechanism comprises an arm pivotally affixed to the frame, the arm adapted to engage the threaded extension to create a constant bias on the threaded extension to force the threaded extension against the threaded opening in the frame to prevent backlash therebetween, and wherein the sensing means is affixed to the arm to sense the position of the spool.

- 42. (Previously Presented) The position sensor of claim 41 wherein there is a magnet affixed to the frame and the sensor comprises a Hall effect sensor that cooperates with the magnet to sense the position of the arm.
 - 43. (Previously Presented) A position sensor comprising: a frame;
 - a spool rotatably mounted to the frame;

a cable windable about the spool and having a distal end adapted to be affixed to the object to be sensed, wherein the spool rotates as the cable winds and unwinds in relation to the movement of the object, said spool operable to travel along a substantially linear path in response to the rotational movement of the spool;

a recoil spring that biases the rotational movement of the spool to cause the cable to wind up on the spool, the recoil spring having one end affixed to the rotatable spool and the other end fixed with respect to the frame;

and a sensing means adapted to sense the position of the spool along its substantially linear path.

44. (Previously Presented) The position sensor of claim 43 wherein the recoil spring is a spiral spring having an outer end and an inner end and wherein the

outer end is affixed to the rotatable spool and the inner end is fixed with respect to the frame.

- 45. (Previously Presented) The position sensor of claim 44 wherein the inner end of the spiral spring is affixed to a hub that is rotatably fixed with respect to the frame but is movable linearly along with the linear travel of the spool.
- 46. (Previously Presented) The position sensor of claim 45 wherein the spool has a hollowed out area and the spiral spring is located within the hollowed out area within the spool.
- 47. (Previously Presented) The position sensor of claim 46 wherein a cover plate covers the hollowed out area enclosing the spiral spring within the spool.
 - 48. (Previously Presented) A position sensor comprising:
 a frame;
 a spool rotatably mounted to the frame;

a cable windable about the spool and having a distal end adapted to be affixed to the object to be sensed, wherein the spool rotates as the cable winds and unwinds in relation to the movement of the object, said spool operable to travel along a substantially linear path in response to the rotational movement of the spool;

a recoil spring that biases the rotational movement of the spool to cause the cable to wind up on the spool, the recoil spring having an outer end affixed to the rotatable spool and an inner end affixed to a hub that is linearly movable but is prevented from rotational movement with respect to the frame, the hub being affixed to the frame by means of at least one pin that extends between the hub and the frame and the at least one pin slidingly interfits in the hub to allow the hub to move linearly with respect to the frame;

and a sensing means adapted to sense the position of the spool along its substantially linear path.

49. (Previously Presented) A position sensor comprising: a frame;

a spool rotatably mounted to the frame;

a cable windable about the spool and having a distal end adapted to be affixed to the object to be sensed, wherein the spool rotates as the cable winds and unwinds in relation to the movement of the object, said spool operable to travel along a substantially linear path in response to the rotational movement of the spool;

a sensing means adapted to sense the position of the spool along its substantially linear path, the sensing means including a magnet in moveable cooperation with the rotating spool and adapted to translate linearly proximate the Hall effect sensor such that the Hall effect sensor provides a position related signal relative to a position of the magnet.;

the sensor further comprising a reference Hall effect chip mounted in fixed relation to the magnet and a circuit operable to compensate for a difference in outputs for the Hall effect sensor and the reference Hall effect chip.

- 50. (New) The position sensor of claim 1 wherein the sensing means includes an inductive transducer.
- 51. (New) The position sensor of claim 40 wherein the sensing means includes an inductive transducer.
- 52. (New) The position sensor of claim 41 wherein the sensing means includes an inductive transducer.
- 53. (New) The position sensor of claim 43 wherein the sensing means includes an inductive transducer.
- 54. (New) The position sensor of claim 48 wherein the sensing means includes an inductive transducer.